

NEW PRODUCT

STELVIO 1800



Battery Voltage	IU1a Wet 8h Range (C5)	IU1a Wet 12h Range (C5)	IU1a Gel PzV 10-14h Range (C5)	Charging Current	Model
24V	280+340 Ah	450+550 Ah	350+420 Ah	50A	24-50
	340+410 Ah	540+660 Ah	420+510 Ah	60A	24-60
36V	230+280 Ah	360+440 Ah	275+340 Ah	40A	36-40
48V	170+210 Ah	270+330 Ah	210+255 Ah	30A	48-30

Sector
of application



Certifications



CHARGING PHASE



CHARGING COMPLETED



ANOMALY



Main features:

- Power up to 1.8 kW
- 24V up to 48V
- 30A up to 60A
- Flexible compact charger with premium features
- Available on-board (-E)
off-board (-W)

Dimensions (LxWxH): 377 x 188 x 79 mm

14.8 x 7.40 x 3.11 in

Weight: 5,5 Kg - 12,13 lbs

Protection Grade: IP20

Input Voltage: 200-240 Vac

Main features:

- SLIM FORM FACTOR FOR ON BOARD and OFF BOARD INSTALLATION
- ACTIVE PFC
- Input Voltage : 200-240 Vac 50-60 Hz
- RESONANT TECHNOLOGY
- HIGH EFFICIENCY: >90%
- SUITABLE FOR LEAD (WET/GEL/AGM) and LITHIUM BATTERIES
- BATTERY THERMAL PROBE I/O (OPT.)
- REMOTE LED (OPT.)
- INTERLOCK (NO/NC)
- AUXILIARY OUTPUT RELAY
- CANBUS - RS485
- REAL TIME CALENDAR (OPT)
- WALL MOUNTING HOLES for easy wall mount

